

Pneumatic diaphragm pump

170 l/min

Item number:	19 062
EAN:	4103810190629
Discount group:	D

Technical data

Delivery rate under free discharge (l/min):	170 (water)
Max. air pressure (bar):	8
Min. air pressure (bar):	2
Max. particle size (mm):	7,5
Max. suction height, dry (m):	6
Max. suction height, wet (m):	9,8
Max. discharge height (m):	80
Max. operating temperature (°C):	65
Min. operating temperature (°C):	-4
Loudness level at 8 bar (db A):	75
Max. air consumption (l/min):	depending on delivery volume and delivery head
Connection air:	1/2" BSP
Connection suction side:	1" BSP
Connection discharge side:	1" BSP
Material pump housing:	PP
Material air diaphragm:	Hytrel®
Material fluid diaphragm:	PTFE
Material ball:	PTFE
Material ball valve seat:	PP
Material O-rings:	FPM
Dimensions LxWxH (mm):	370 x 222 x 370
Weight (kg):	15

Specification

- Fixture, for wall-mounting
- Accessories required:
- Wall mounting bracket (87 919)
- Quick release adapter (20 066)
- Suitable for:
- Fresh and waste oils, water, AdBlue®
- Water-based liquids, to which PP and PTFE are resistant, e.g. glass cleaner and radiator antifreeze agents

Packaging

Dimensions LxWxH (mm):	430 x 260 x 460
Weight including package (kg):	15,5
Packing unit:	1,0