

Waste oil drainer unit-75 l

mobile-pneumatic pump 1:1

Item number:	27 040
EAN:	4103810270406
Discount group:	D

Technical data

Total volume (l):	75
Telescopic height level of drain bowl (mm):	1180 - 1750
Volume of drain bowl (l):	18
Diameter drain bowl (mm):	420
Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Discharge:	via pneumatic pump 1:1
Connection drainage:	hydraulic coupling, size 4, G 3/4" female
Lacquering of container:	window grey, satin, RAL 7040
Lacquering of drain bowl:	blue, Pantone 294 C
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	600 x 580 x 1150
Weight (kg):	33,5

Specification

- Float full level indicator
- Pneumatic pump 1:1, for discharge of waste oil drainer, male quick release adapter G1/4", NW 7,2 (20 062)
- Lever ball valve
- Dispensing hose, 2 m, with hydraulic coupling, size 4, G 3/4" female (19 770), correspondent connecting plug, size 4, G 3/4" female (19 774), enclosed for connection to oil distribution lines or to waste oil collecting tanks
- 2 fixed rear wheels, 2 castor front wheels
- Drain bowl with removable strainer and drain grill
- Sturdy handle
- Container made from 1,5 mm sheet steel
- With metal protective cover to avoid damage
- Lacquered with oil-resistant hydro-structure paint
- With height adjustable drain bowl

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)
- If the waste oil drainer is discharged via a pipe system into an oil collection tank, it is recommended to use an overflow protection valve. Please adhere to regional regulations and guidelines of your country

Packaging

Dimensions LxWxH (mm):	780 x 580 x 630
Weight (kg):	36
Packing unit:	1,0