
GDW280V/FS2



Power Rating		
Emergency Standby Power ESP	kVA	275.0
Emergency Standby Power ESP	kW	220.0
Prime power PRP	kVA	250.0
Prime power PRP	kW	200.0
Voltage	V	400/230
Frequency	Hz	50
Power factor	cos ϕ	0.8
Phases		3
Fuel		Diesel





Ratings definition (ISO-8528-1)
ESP - Emergency Standby Power:
It is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.
PRP - Prime Power:
It is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output over 24 h of operation shall not exceed 70 % of the prime power.
G2 class load acceptance in accordance with ISO 8528-5: Higher performance classes check upon request.
Gensets are compliant with EC mark which includes the following directives and standards and subsequent modification and intregation:
• 2006/42/CE Machinery safety
• 2014/30/UE Electromagnetic compatibility
• 2014/35/UE electrical equipment designed for use within certain voltage limits
• 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC) – If applicable
• 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2016/1628 EC) – If applicable
• ISO 8528 as applicable
• 2011/65 ROHS
• EN 12100, EN 13857, EN 60204 as referred into the ISO8528-13
Company with quality certification ISO 9001


www.pramac.com

Data Centre Power (available with DCP optional)



Power Rating DCP

Data Center Power DCP	kVA	250.0
Data Center Power DCP	kW	200.0
Voltage	V	400/230
Frequency	Hz	50
Power factor	cos ϕ	0.8
Phase		3
Fuel		Diesel



Ratings definition (ISO-8528-1)

DCP - Data center power:
It is the maximum power which a generating set is capable of delivering while supplying a variable or continuous electrical load and during unlimited run hours.
Applies to data center installations where a reliable power infrastructure is available.
Prolonged operation at load in parallel with a utility is not permitted.

For specific transient reactance, verify with your local sales distributor.

www.pramac.com

Engine specifications		
Engine brand		Volvo
Model		TAD841GE
Operation Speed Nominal	rpm	1500
Engine cooling system		Water
Nr. of cylinder and disposition		6 in line
Displacement	cm³	7700
Aspiration	Type	Turbocharged
Gross Engine Power ESP	kWm	254
Gross Engine Power PRP	kWm	232
Gross Data Center Power DCP	kWm	232
Fan Power	kWm	12
Fan Air flow	m³/min	294
Total Oil capacity	l	27
Total Coolant capacity	l	36
Fuel		Diesel
Specific Fuel consumption 100% ESP	g/kWh	198
Specific Fuel consumption 75% PRP	g/kWh	204
Starting system		Electric
Electric circuit	V	24



Alternator specifications		
Alternator brand		Mecc Alte
Model		ECO38 2M4 C
Winding		Standard
Winding Connections	Type	Series Star
Frequency	Hz	50
Voltage	V	400
Phases		3
Power factor	cos ϕ	0.8
Stand-by rating 27°C	kVA	275
Continuous Nominal Rating 40°C	kVA	250
Efficiency @ 100% of load	%	93.4
Type		Brushless
Poles		4
Voltage tolerance	%	1
Class		H
IP protection		23



Installation data		
Total air flow	m³/min	342
Exhaust gas flow PRP	m³/min	42
Exhaust gas temperature	°C	478
Fuel consumption 75% PRP	l/h	41.79
Fuel consumption 100% PRP	l/h	53.30



www.pramac.com

Fuel Tank - Options Available:		
To be ordered with equipment (when necessary)		
AUTONOMY		
8PFT Running time 75% PRP	h	8.38
MFT-XS Running time 75% PRP	h	11.96
MFT-S Running time 75% PRP	h	14.36
MFT-M Running time 75% PRP	h	23.93
MFT-L Running time 75% PRP	h	52.64



PFT	Plastic Fuel Tank	Type	8
	8PFT Fuel tank capacity	l	350
	8PFT Fuel tank location		Internal
	.		
MFT	Metal Fuel Tank	Type	XS
	MFT-XS Fuel tank capacity	l	500
	MFT-XS Fuel tank location		Internal
	.		
MFT	Metal Fuel Tank	Type	S
	MFT-S Fuel tank capacity	l	600
	MFT-S Fuel tank location		Internal
	.		
MFT	Metal Fuel Tank	Type	M
	MFT-M Fuel tank capacity	l	1000
	MFT-M Fuel tank location		With sub-base
	MFT-M EXTRA Length (only for open versions)	mm	647
	MFT-M EXTRA Height (for open/canopy versions)	mm	340
	MFT-M EXTRA Weight	kg	548
	.		
MFT	Metal Fuel Tank	Type	L
	MFT-L Fuel tank capacity	l	2200
	MFT-L Fuel tank location		With sub-base
	MFT-L EXTRA Length (only for open versions)	mm	647
	MFT-L EXTRA Height (open/canopy versions)	mm	655
	MFT-L EXTRA Weight	kg	826





Electrical Data		
Battery Voltage	V	24
Genset Voltage	V	400/230
Frequency	Hz	50
Phases		3
Power Factor	cos ϕ	0.8
Max current	A	397
Nominal current	A	361
Circuit breaker	A	400



www.pramac.com

Control panel - Options Available:

AUTOMATIC CONTROL PANEL	ACP
MODULAR PARALLEL PANEL	MPP



ACP - AUTOMATIC CONTROL PANEL

- Auto Mains Failure (AMF) function
- Gen-set controller for single genset operating in standby or prime power modes
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of remote control modules available as option
- Wide range of I/O expansion modules available as option

Power supply by circuit breaker and/or terminal bus bar



MPP - MODULAR PARALLEL PANEL

- Modular parallel panel allows the genset to work in parallel (up to 32 gen-sets)
- Easy switching between parallel to mains or multiple genset applications
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of communication and connection capabilities available

Power supply by circuit breaker and/or terminal bus bar



CONTROL PANEL - Optional Equipment:

Differential Protection	ADI



www.pramac.com


OPEN VERSION

- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Screwed support legs
- Hole for handling by crane
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground



Dimensional data Open Version

Length	(L) mm	3055
Width	(W) mm	1200
Height	(H) mm	1795



Weight	kg	2033

OPTIONS AVAILABLE (ONLY FOR OPEN VERSION)

Industrial Exhaust System	IES
Residential Exhaust System	RES
Critical Exhaust System	CES




CANOPY VERSION

- Weatherproof Enclosure made of galvanized sheet metal allows to protect genset from corrosion and aggressive condition
- Soundproofed enclosure tanks to high quality soundproof material and residential silencer, allows to have low noise emission level
- Big large lateral doors allows an easy service and maintenance operation
- Doors equipped with key lockable handles
- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Screwed support legs
- Hole for handling by crane
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground



Dimensional data Canopy Version

Length	(L) mm	3702
Width	(W) mm	1200
Height	(H) mm	2050



Weight	kg	2563

Noise Level Canopy Version

Guaranteed noise level (LWA)	dB(A)	97
Noise pressure level @ 1 m	dB(A)	78
Noise pressure level @ 7 m	dB(A)	68



www.pramac.com


CANOPY EXTRA SILENT VERSION

- Extra silent Enclosure with low noise emission, suitable for installation near city centre and in any place where severe noise emission restriction are present
- Extra Silent Enclosure guarantee very low noise emission thanks to an additional soundproofing modules, high quality soundproof material and residential silencer installed inside the enclosure
- Weatherproof Enclosure made of galvanized sheet metal allows to protect genset from corrosion and aggressive condition
- Big large lateral doors allows an easy service and maintenance operation
- Doors equipped with key lockable handles
- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Screwed support legs
- Hole in the baseframe for handling by crane
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground



Dimensional data Canopy (Extra Silent Enclosure)

Length	(L) mm	3950
Width	(W) mm	1200
Height	(H) mm	2520



Weight	kg	3285

Noise Level Canopy (Extra Silent Enclosure)

Guaranteed noise level (LWA)	dB(A)	94
Noise pressure level @ 1 m	dB(A)	75
Noise pressure level @ 7 m	dB(A)	64




OPTIONS AVAILABLE (ONLY FOR CANOPY VERSIONS)

Roof lifting Point	RLP



OPTIONAL FEATURES

To be ordered with equipment (when necessary)	:
Pre-Heating System	PHS
Heavy-Duty Air Filter	HDF
Water Separator Filter	WSP
Exhaust Spark Arrestor	ESA
Hot Parts Protection	HPP
Alternator Winding Total Protection	WTP
Alternator anti-condensation heater	ACH
Galvanized skid base with fork lift point	GSB



www.pramac.com

The information is aligned with the Data file at the time of download.
Printed on 22/04/2026 (ID 15228)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc.| All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

PRAMAC