
GSW1290B



Power Rating		
Emergency Standby Power ESP	kVA	1283
Emergency Standby Power ESP	kW	1026
Prime Power PRP	kVA	1162
Prime Power PRP	kW	930
Voltage	V	400/230
Frequency	Hz	50
Power factor	cos ϕ	0.8
Phase		3
Fuel		Diesel






Ratings definition (ISO-8528-1)
ESP - Emergency Standby Power:
It is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.
PRP - Prime Power:
It is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output over 24 h of operation shall not exceed 70 % of the prime power.
G2 class load acceptance in accordance with ISO 8528-5: Higher performance classes check upon request.
Gensets are compliant with EC mark which includes the following directives and standards and subsequent modification and intregation:
• 2006/42/CE Machinery safety
• 2014/30/UE Electromagnetic compatibility
• 2014/35/UE electrical equipment designed for use within certain voltage limits
• 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC) – If applicable
• 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2016/1628 EC) – If applicable
• ISO 8528 as applicable
• 2011/65 ROHS
• EN 12100, EN 13857, EN 60204 as referred into the ISO8528-13
Company with quality certification ISO 9001

www.pramac.com

Engine specifications		
Engine Brand		Baudouin
Model		12M33 G1250/5
Operating Speed-Nominal	rpm	1500
Engine cooling system		Water
[50Hz] Exhaust emission level		Non Emission Certified
Nr. of cylinder and disposition		12 V angle
Displacement	cm³	39200
Aspiration		Turbocharged aftercooled
Speed governor		Electronic
Maximum gross power LTP ESP	kW	1108
Prime gross power PRP	kW	1007
Oil capacity	l	160
Lube oil consumption PRP (max)	%	0.3
Coolant capacity	l	83
Fuel		Diesel
Specific fuel consumption 75% PRP	g/kWh	194.6
Starting system		Electric
Starting engine capability	kW	10
Electric circuit	V	24



Radiator

Cooling fan	Electric

Alternator Specifications		
Alternator		Mecc Alte
Model		ECO43-2LN/4
Windings connection		Parallel Star
Frequency	Hz	50
Voltage	V	400
Phase (s)		3
Power factor	cos ϕ	0.8
Emergency peak power 163°/27°	kVA	1420
Efficiency @ 75% load	%	96.2
Type		Brushless
Poles		4
Voltage regulation system		Electronic
Standard AVR		DER1
Voltage tolerance	%	0.5
Class		H
IP protection		23
Cooling air	m³/s	1.5




www.pramac.com

Genset Equipment - Basic Configurations Available		
Battery	n	2
Battery Capacity	Ah	200



Supplements available:

Manual Battery Switch	MBS
Fully bunded base frame	FBD
Leakage detection sensor (only with FBD)	LDS
Fuel Cut Off Valve	FCV
Automatic Fuel Pump	AFP
Double Automatic Fuel Pump	DFP
Coolant Pre-Heating System	PHS
Automatic Lube Oil Top Up System with lube oil tank	ALS
Other Configurations and-or special versions available on requests	.



Installation data		
Total air flow	m³/min	1299
Exhaust gas flow	m³/min	204.6
Exhaust gas temperature	°C	550
Fuel consumption 100% PRP	l/h	236.17
Fuel consumption 75% PRP	l/h	176.83



Electrical Data		
Battery Voltage	V	24
Genset Voltage	V	400/230
Frequency	Hz	50
Phases		3
Power Factor	cos ϕ	0.8
Nominal current	A	1677
Max current	A	1852
Circuit breaker	A	2000



www.pramac.com

Control panel - Options Available:

AUTOMATIC CONTROL PANEL	ACP
MODULAR PARALLEL PANEL	MPP



ACP - AUTOMATIC CONTROL PANEL


- Auto Mains Failure (AMF) function
- Gen-set controller for single genset operating in standby or prime power modes
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of remote control modules available as option
- Wide range of I/O expansion modules available as option

Power supply by circuit breaker and/or terminal bus bar




ACP - Power Panel - Breakers Available:

GCB1 - Genset Circuit Breaker 3-pole	A	2000
GCB2 - Genset Circuit Breaker 4-pole	A	2000
ETB - External Terminal Board (with GCB)		Standard



LTS - Load Transfer Switch [Accessories for ACP Automatic Control Panel]

The Load Transfer Switch (LTS) panel operates the power supply changeover between the generator and the Mains in stand-by applications, guaranteeing load supply in a short period of time. LTS fit inside a sturdy standalone cabinet which can be installed separate from the generating set. The logic control of LTS is operated by the Automatic Control Panel (ACP) of the generating set.



MPP - MODULAR PARALLEL PANEL


- Modular parallel panel allows the genset to work in parallel (up to 32 gen-sets)
- 7" full colour display
- Easy switching between parallel to mains or multiple genset applications
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of communication and connection capabilities available

Power supply by terminal bus bar



MPP - Power Panel - Breakers Available:

GMB1 - Genset Circuit Breaker 3-pole motorized	A	2000
GMB2 - Genset Circuit Breaker 4-pole motorized	A	2000
ETB - External Terminal Board (with GMB)		Standard



www.pramac.com

OPEN VERSION

- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Lifting points on the baseframe for handling by crane
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground




Dimensional data Open Version

Length	(L) mm	4680
Width	(W) mm	2100
Height	(H) mm	2550
Weight	kg	9186

OPTIONS AVAILABLE (ONLY FOR OPEN VERSION)

Industrial Exhaust System	IES
Residential Exhaust System	RES




CANOPY VERSION

- Weatherproof Enclosure made of galvanized sheet metal allows to protect genset from corrosion and aggressive condition
- Soundproofed enclosure tanks to high quality soundproof material and residential silencer, allows to have low noise emission level
- Big large lateral doors allows an easy service and maintenance operation
- Doors equipped with key lockable handles
- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground
- Lifting points on the enclosure for handling by crane



Dimensional data Canopy Version

Length	(L) mm	7800
Width	(W) mm	2434
Height	(H) mm	2989
Weight	kg	12835



Noise Level Canopy Version

Noise pressure level @ 7 m	dB(A)	77+/-3

www.pramac.com

CONTAINER VERSION

- Soundproofed Container adaptable to meet all your requirements and needs, equipped with residential silencer positioned inside or on the roof.
- Sturdy structure similar to shipping containers: upper and lower corner castings, monolithic structure, walls and roof made of corrugated steel sheet.
- Reinforced floor structure covered with teardrop patterned steel sheet
- High resistance to the atmospheric agents.
- Air inlet and exhaust openings air outlet for genset cooling.
- Large lateral doors allows an easy service and maintenance operation.
- Doors fixed by sturdy steel hinges equipped with lever bolt locks and panic bars.



Dimensional data Container Version

Length	(L) mm	12192
Width	(W) mm	2438
Height	(H) mm	2896

Noise Level Container Version

Noise pressure level @ 7 m	dB(A)	77 +/-3

www.pramac.com

The information is aligned with the Data file at the time of download.
Printed on 29/04/2026 (ID 17184)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc.| All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice