
GSW2266P



Power Rating		
Emergency Standby Power ESP	kVA	2268
Emergency Standby Power ESP	kW	1814
Prime Power PRP	kVA	2021
Prime Power PRP	kW	1617
Voltage	V	400/230
Frequency	Hz	50
Power factor	cos ϕ	0.8
Phase		3
Fuel		Diesel






Ratings definition (ISO-8528-1)
ESP - Emergency Standby Power:
It is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.
PRP - Prime Power:
It is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output over 24 h of operation shall not exceed 70 % of the prime power.
G2 class load acceptance in accordance with ISO 8528-5: Higher performance classes check upon request.
Gensets are compliant with EC mark which includes the following directives and standards and subsequent modification and intregation:
• 2006/42/CE Machinery safety
• 2014/30/UE Electromagnetic compatibility
• 2014/35/UE electrical equipment designed for use within certain voltage limits
• 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC) – If applicable
• 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2016/1628 EC) – If applicable
• ISO 8528 as applicable
• 2011/65 ROHS
• EN 12100, EN 13857, EN 60204 as referred into the ISO8528-13
Company with quality certification ISO 9001

www.pramac.com

Engine specifications		
Engine Brand		Perkins
Model		4016-61TRG2
Operating Speed-Nominal	rpm	1500
Engine cooling system		Water
[50Hz] Exhaust emission level		Unregulated
Nr. of cylinder and disposition		16 V
Displacement	cm^3	61123
Aspiration		Turbocharged
Speed governor		Electronic
Maximum gross power LTP ESP	kW	1985
Prime gross power PRP	kW	1774
Fan consumption	kW	100
Oil capacity	l	213
Coolant capacity	l	95
Fuel		Diesel
Specific fuel consumption 75% PRP	g/kWh	195
Starting system		Electric
Starting engine capability	kW	16.4
Electric circuit	V	24



Alternator Specifications		
Alternator		Mecc Alte
Model		ECO46-1LN/4
Windings connection		Parallel Star
Frequency	Hz	50
Voltage	V	400
Phase (s)		3
Power factor	cos ϕ	0.8
Emergency peak power 163°/27°	kVA	2268
Efficiency @ 75% load	%	96.8
Type		Brushless
Poles		4
Voltage regulation system		Electronic
Standard AVR		M3K
Voltage tolerance	%	0.5
Class		H
IP protection		23
Cooling air	m^3/s	2.25




www.pramac.com

Genset Equipment - Basic Configurations Available		
Battery	n	4
Battery Capacity	Ah	200
INTEGRATED FUEL TANK - VERSIONS AVAILABLE		:
IFT1 - Integrated Fuel Tank (steel)	l	500
IFT2 - Integrated Fuel Tank (steel)	l	1000



Supplements available:

Manual Battery Switch	MBS
Fully bunded base frame	FBD
Leakage detection sensor (only with FBD)	LDS
Fuel Cut Off Valve	FCV
Automatic Fuel Pump	AFP
Double Automatic Fuel Pump	DFP
Coolant Pre-Heating System	PHS
Automatic Lube Oil Top Up System with lube oil tank	ALS
Other Configurations and-or special versions available on requests	.



Installation data		
Exhaust gas flow	m³/min	490
Exhaust gas temperature	°C	489
Fuel consumption 100% PRP	l/h	416.04
Fuel consumption 75% PRP	l/h	314.07
IFT1 - Running time 75% PRP	h	1.59
IFT2 - Running time 75% PRP	h	3.18



Electrical Data		
Battery Voltage	V	24
Genset Voltage	V	400/230
Frequency	Hz	50
Phases		3
Power Factor	cos ϕ	0.8
Nominal current	A	2918
Max current	A	3274
Circuit breaker	A	3200



www.pramac.com

Control panel - Options Available:

AUTOMATIC CONTROL PANEL	ACP
MODULAR PARALLEL PANEL	MPP



ACP - AUTOMATIC CONTROL PANEL


- Auto Mains Failure (AMF) function
- Gen-set controller for single genset operating in standby or prime power modes
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of remote control modules available as option
- Wide range of I/O expansion modules available as option

Power supply by circuit breaker and/or terminal bus bar




ACP - Power Panel - Breakers Available:

GCB1 - Genset Circuit Breaker 3-pole	A	3200
GCB2 - Genset Circuit Breaker 4-pole	A	3200
ETB - External Terminal Board (with GCB)		Standard



LTS - Load Transfer Switch [Accessories for ACP Automatic Control Panel]

The Load Transfer Switch (LTS) panel operates the power supply changeover between the generator and the Mains in stand-by applications, guaranteeing load supply in a short period of time. LTS fit inside a sturdy standalone cabinet which can be installed separate from the generating set. The logic control of LTS is operated by the Automatic Control Panel (ACP) of the generating set.



MPP - MODULAR PARALLEL PANEL


- Modular parallel panel allows the genset to work in parallel (up to 32 gen-sets)
- 7" full colour display
- Easy switching between parallel to mains or multiple genset applications
- Full gen-set monitoring and protection
- Detailed event and performance log with time and date
- Wide range of communication and connection capabilities available

Power supply by terminal bus bar



MPP - Power Panel - Breakers Available:

GMB1 - Genset Circuit Breaker 3-pole motorized	A	3200
GMB2 - Genset Circuit Breaker 4-pole motorized	A	3200
ETB - External Terminal Board (with GMB)		Standard



www.pramac.com


OPEN VERSION

- Baseframe made of welded steel profile
- Anti-vibration mountings properly sized
- Lifting points on the baseframe for handling by crane
- Moving and rotating parts protection against accidental contact
- Grounding point to connect all metal parts to ground




Dimensional data Open Version

Length	(L) mm	6300
Width	(W) mm	2180
Height	(H) mm	2738



OPTIONS AVAILABLE (ONLY FOR OPEN VERSION)

Industrial Exhaust System	IES
Residential Exhaust System	RES




CONTAINER VERSION

- Soundproofed Container adaptable to meet all your requirements and needs, equipped with residential silencer positioned inside or on the roof.
- Sturdy structure similar to shipping containers: upper and lower corner castings, monolithic structure, walls and roof made of corrugated steel sheet.
- Reinforced floor structure covered with teardrop patterned steel sheet
- High resistance to the atmospheric agents.
- Air inlet and exhaust openings air outlet for genset cooling.
- Large lateral doors allows an easy service and maintenance operation.
- Doors fixed by sturdy steel hinges equipped with lever bolt locks and panic bars.



Dimensional data Container Version

Length	(L) mm	12192
Width	(W) mm	2459
Height	(H) mm	4307



Noise Level Container Version

Noise pressure level @ 7 m	dB(A)	77 +/-3

The information is aligned with the Data file at the time of download.
Printed on 24/04/2026 (ID 17237)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc.| All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

www.pramac.com