

Tank-400 l-double walled-SR-MO

steel-HDPE

Item number:	45 090
EAN:	4103810450907
Discount group:	D

Technical data

Tank volume (l):	400
Material outer container:	steel, hot-dip galvanized
Material of interior container:	HDPE (high density polyethylene)
Connections:	4 x G 2" female, drum adapter
External dimensions LxWxH (mm):	730 x 700 x 1180
Empty weight (kg):	55

Specification

- Mechanical float level indicator
- Optical leakage indicator
- Integral handles
- Steel pallet foot, fully detachable

Special notes

- With UN-approval D/BAM/6403/31HA1
- For above ground storage in closed rooms
- to be utilized stationary (SR) and mobile (MO)
- Suitable for:
- fuel oil and diesel
- Used engine- and gearbox oil (used oil) of known origin according to company safety standards
- Lubricating oil L-AN, acc. to DIN 51501 (the lubricating oils AN 5 and AN 7 are not easily inflammable liquids, hazard class A III, acc. to VbF)
- Engine- and lubricating oils acc. to DIN 51 511
- Gear oils for motor vehicles, acc. to DIN 51512
- Hydraulic oils H, HL and HL-P, acc. to DIN 51524 / 51525
- Heat transfer oil Q, acc. to DIN 51 522
- Synthetic oils
- Rapeseed Oil Methyl Ester (RME)

Packaging

Packing unit:	1,0