



mobiSTEEL-2000 I-double-walled

steel-tank accessories-230 V-65 I-F

Item number:	26 782 960
EAN:	4103810423147
Discount group:	D

Technical data

Tank	
Tank volume (l):	2000
UN approval:	un 31A/Z/....*/PL/SPAW-MAL/4565/2536
UN certificate:	UN/16/1501/11
Material of container:	Steel sheet
Material of end caps:	Steel sheet
Wall thickness (mm):	3
Color of container:	grey, RAL 7042
Colour of cover:	grey, RAL 7042
Pump	
Brand:	FMT Swiss AG
Connecting cable, length (m):	2
Pump design:	vane pump, selfpriming
Duty cycle (min):	continuous operation – a real endurance runner
Hydraulic data	
Delivery rate under free discharge (l/min):	65
Discharge pressure up to (bar):	1,8
Pumping media:	fuel oil and diesel
Motor data	
Voltage (V):	230
Power consumption (A):	3
Safety class:	IP66
Digital in-line meter	
Temperature range (°C):	-10 / +60
Display:	5 digits display
Dimensions LxWxH (mm):	2580 x 1180 x 1270
Empty weight (kg):	836

Specification

- Double wall steel tank (45 202)
- Tank truck connector (80 514)
- Level indicator (83 465 100)
- Overfill sensor (83 723)
- Ventilation valve (45 140)
- 1 Piece suction set G 1" for pump with vane, suction hose, non return valve and drainer (89 010 010)
- 1 Piece suction set G 3/4" for power generator with suction hose, non return valve and drainer (89 010 001)
- 1 piece connection for return line G 1/2" from power generator (89 010 002)
- Universal securing trap for shackle
- Lockable cap
- Vane pump, with integral bypass (23 430)

- Diesel-exchange filter, 30 µm (23 209)
- Automatic nozzle valve with swivel joint, ZVAD (23 176)
- In-line meter, digital (23 190)
- Discharge hose, 6 m, DN 19, G 1" male, G 1" female (23 155 958)

Special notes

- European ADR Certificate for transportation of dangerous liquids on public roads
- Fillable up to 90 % and transportable according to ADR
- Transportable by forklift and crane lugs
- 2 tanks could be stacked
- Integrierter Filter hält Kondenswasser zurück
- Level indicator, mechanical
- Manhole enables access to the inner tank
- 3 outlets for delivery/gazole return with closed cover

Packaging

Dimensions LxWxH (mm):	2580 x 1180 x 1270
Weight (kg):	836
Packing unit:	1,0