

Pulse meter-G 1" fem-G 1" fem

oval gear meter-stainl. steel

Item number:	23 823
EAN:	4048358238238
Discount group:	D

Technical data

Distance in-/out flange (mm):	95
Connection:	G 1" female
Medium:	AdBlue®
Flow capacity min. (l/min):	2
Flow capacity max. (l/min):	100
Pre-set flow direction:	horizontal
Permitted liquid temperature max. (°C):	35
Permitted ambient temperature (°C):	-5 / +35
Measuring accuracy (%):	0,5
Nominal pressure (bar):	3,5
Burst pressure (bar):	28
Pulses (pulses/l):	23,15
Contact-form:	A-shut-up device
Switching capacity (W):	10
Operating voltage (V):	3 - 30 V DC
Operating current (A):	0,5
Switch stream (A):	0,5
Sensor resistor (mOhm):	300
Materials of parts in contact with liquid	
Meter housing:	stainless steel
Oval gears:	POM
Seals:	NBR 70
External dimensions LxWxH (mm):	100 x 100 x 65
Weight (kg):	1,38

Specification

- Pulse generator for the Fluid Management System in stainless steel

Special notes

- Suitable for the use with AdBlue®

Packaging

Packaging:	Carton
Dimensions LxWxH (mm):	145 x 126 x 78
Weight including package (kg):	1,46
Packing unit:	1,0