

Hose end meter-digital

oval gears-for aqueous solutions

Item number:	19 700
EAN:	4048358197009
Discount group:	D

Technical data

Connection:	G 1/2" i BSP
Nominal width:	DN 12
Metering principle:	oval gears
Media:	cooling liquid, anti-freeze
Flow capacity (l/min):	1 - 35
Viscosity (mPa s):	8 - 5000
Nominal pressure (bar):	70
Operating pressure min. (bar):	0,35
Temperature range (°C):	-10 / +50
Measuring accuracy (%):	± 0,5
Repetition tolerance (%):	± 0,3
Solution (l):	0,002
Pulses (pulses/l):	216
Design:	Can not be calibrated for public sales (NEF)
Housing material:	Aluminium die casting
Display:	digital, three digits and two decimal digits
Height of the digits (mm):	8
Battery type:	LR1 1,5 V
Battery lifetime:	approx. 2 years at 0.5 hours per day (20 °C)
Weight (kg):	1,92

Specification

- Discharge hose with 90° angle and manual non-drip nozzle
- Swivel joint (19 616)
- Valve

Special notes

- Housing including the chamber for electronics are made of aluminium, cast-rinde will not be finished
- Impact-resistant electronics
- Easy to read 5-digits display
- Resettable display
- Rubber buffer provides shock prevention in case of rough use.
- The metering precision can be adjusted to the viscosity using the calibration scale
- The user can adjust the following indicating units: Litres + gallons

Packaging

Dimensions LxWxH (mm):	590 x 120 x 155
Weight including package (kg):	2,06
Packing unit:	1,0