

Tank-1500 l-double walled-SR

steel-HDPE-waste oil

Item number:	45 108
EAN:	
Discount group:	D

Technical data

Tank volume (l):	1500
Connection:	4 x G 2" female, drum adapter
Material outer container:	steel, hot-dip galvanized
Material of interior container:	HDPE
Dimensions LxWxH (mm):	1630 x 755 x 1870
Empty weight (kg):	180

Specification

- Mechanical float level indicator
- Optical leakage indicator
- Integral handles
- Steel plate foot
- Ventilation valve (45 140 950)
- Suction tube (19 460 397)

Special notes

- With general construction authorities approval no. Z-40.21-283 of German DIBt-Berlin
- For above ground storage in closed rooms
- Stationary
- Suitable for:
- fuel oil and diesel
- Used engine- and gearbox oil (used oil) of known origin according to company safety standards
- Lubricating oil L-AN, acc. to DIN 51501 (the lubricating oils AN 5 and AN 7 are not easily inflammable liquids, hazard class A III, acc. to VbF)
- Engine- and lubricating oils acc. to DIN 51 511
- Gear oils for motor vehicles, acc. to DIN 51512
- Hydraulic oils H, HL and HL-P, acc. to DIN 51524 / 51525
- Heat transfer oils Q according to DIN 51 522
- Synthetic oils
- Rapeseed Oil Methyl Ester (RME)

Packaging

Packing unit:	1,0