







Barrel pump for gasoline-G 2" -S 56x4

SRL 355-955-24 l/min

Item number:	13 045
EAN:	4103810130458
Discount group:	A

Technical data

Delivery rate at 60 strokes/min (l/min):	24
Pumping media:	special fuels, class AI-III fuel (gasoline), diesel, heating oil, petroleum, low viscosity oils up to SAE 50, antifreeze and windscreen antifreeze (diluted or undiluted)
Delivery rate (l/stroke):	0,4
Usage:	container 60/200/220 l
Length, three-part suction pipe (mm):	355 - 955
Barrel screw coupling:	G 2" male and S 56x4

Materials of parts in contact with liquid

Pump body:	ABS + PA6
Seals:	FKM
Metal pieces:	stainless steel

Weight (kg):	2,35

Specification


- Telescopic suction tube (13 094) with filter (13 097 004), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085) and barrel screw coupling S 56x4 (13 085 001)
- Complete transfer hose set - (13 045 010) with non-electric conductive hose 1500 mm (81 679), steel spout hook (00 844), hose holder (00 845) and grounding cable with alligator clip
- Discharge spout (13 098)
- Valuable sales package


Special notes


- Constant delivery rate
- Completely dismountable - easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Can be freely positioned in 30° increments
- Optional barrel adapters: barrel adapter S 56x4 (13 085 001); barrel adapter S 69,5x5,5 (13 085 002); barrel adapter M 64x4 male (13 085 003); barrel adapter S 64x5 (13 085 006)
- 5 year warranty (excluding wearable parts)
- Telescopic suction tube, flexible length (13 094)
- Described as a safe solution for gas explosion risk areas as well as support for petrol fuels

Packaging

Dimensions LxWxH (mm):	395 x 243 x 125
Weight including package (kg):	2,63
Packing unit:	1,0


S 56x4
G 2"


244
teleskopierbar von 683 bis 955 mm
teleskopierbar von 355 bis 627 mm


142