









## FMS set for diesel

| | |
|---|---|
| **Item number:** | 23 497 |
| **EAN:** | 4048358234971 |
| **Discount group:** | D |

### Technical data

| | |
|---|---|
| Number of users: | 1000 |
| Number of vehicles: | 1000 |
| Number of vehicles per user: | 50 |
| Type of user ID: | PIN and/or iButton |
| Type of display and size: | illuminated 5"-LCD display |
| Compatible operating systems: | Linux, MAC, Windows |
| Voltage (V): | 230 |
| Frequency (Hz): | 50 |
| Power consumption (A): | 0,25 |
| Safety class: | IP54 |
| Anschlusskabel mit Eurostecker, Länge (m): | 2 |
| Maximum settable dispensing quantity (l): | 0-999 |
| The tank level for re-filling can be adjusted when the tank is empty (L): | 0-999 |
| Note | |
| The level for re-filling will be arithmetically calculated | |
| Number of filling stations: | 2 |
| Dimensions LxWxH (mm): | 240 x 156 x 56 |

### Specification

- SD card (84 023)
- SD card reader for USB port (84 235)
- Software and operating instructions on CD-ROM
- 7 iButtons in black for users (5 pcs), red for service (1 pc) and green for supervisor (1 pc)
- Control nozzle storage bracket (23 066) with cable, 3 m, and connecting plug (83 012) for connection with FMS
- Pulse meter (IPG) (23 820) with cable, 3 m and connecting plug (83 012)
- Fluid Management System (FMS) in aluminium housing (23 499)

### Special notes

- An integral heating in the FMS provides an operation and a clearness of the display even at low temperatures (tested until -25 °C).
- Two tanks can be operated with the FMS
- User identification by PIN and/or by iButton
- User friendly PC application for configuration and installation of storage tanks, tank volumes, users and vehicles
- The PC application checks for available updates every 10 days
- All data can be installed on a PC and can be transferred with a SD card to the FMS
- The data of any refilling process can be readout on a PC and can be exported for special analysis. A USB adapter for the SD card is part of the product.
- The SD card supplied offers space for the storage of several thousands of refilling processes.

**Packaging**

| | |
|---|---|
| Dimensions LxWxH (mm): | 370 x 225 x 205 |
| Packing unit: | 1,0 |