

Grease gun-G 1/8" fem-EBZD

GRDR-Rectus coupling-type 72

Item number:	18 102 952
EAN:	4103810424977
Discount group:	D

Technical data

Connection 1:	G 1/8" female
Connection 2:	Rectus coupler, type 72, NW 6 mm, for quick release adapter Rectus
Operating pressure max. (bar):	400
Application range:	NLGI 0 up to NLGI 3
Operating temperature (°C):	-10 / +60
Weight (kg):	1,47

Specification

- Grease meter (18 115), 5 digits, display of partial quantity and totalisator, resettable
- Connector G 1/8" – meter/grease gun with nut (92 459)
- Rectus coupler, type 72 (01 297)
- Straight spout
- Z-swivel joint (18 082)
- Packed in carton box
- With EAN bar code

Special notes

- For filling centralized lubrication systems
- Gun body, guard and trigger made of impact and pressure resistant die cast zinc
- Galvanically surface-treated die cast zinc parts
- Low release force at high pressures
- No pressure surge during opening
- Large size hanging bracket
- Ergonomic component design
- Suitable for greases NLGI 0 up to NLGI 3
- Completely dismountable - easy to clean
- Guard for trigger lock
- Spare parts available for 10 years

Packaging

Dimensions LxWxH (mm):	270 x 170 x 130
Weight including package (kg):	1,57
Packing unit:	1,0