

Pneumatic pump 5:1-DW-set

SRL 860-for wall-mounting

Item number:	19 385 600
EAN:	4103810706042
Discount group:	D

Technical data

Length of suction tube (mm):	1200
Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Connection discharge side:	G 1/2" male
Connection container:	G 2" male, drum adapter

Specification

- installation set
- For wall-mounting
- Pneumatic oil pump 5:1 (19 385)
- Double-acting pump, provides a continuous flow of media
- Suction tube, with bend, G 3/4" female
- Wall mounting bracket (19 521)
- Connecting hose, 2 m, G 3/4" i/a, for connecting suction tube / pneumatic pump
- Compressed air hose, 2 m, DN 9, with male quick connecting adapter, for Rectus coupling, type 26
- Oil discharge hose, 2 m, G 1/2" male/female, lever ball valve, G 1/2" female
- Air maintenance unit (20 218 950)
- With all adapters required for assembly
- Designed for use in conjunction with pipe lines. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar).
- Can be easily combined with several hose reels

Packaging

Dimensions LxWxH (mm):	1310 x 190 x 195
Weight (kg):	13
Packing unit:	1,0