

Storage can pump-SRL 500-3 l/min

with barrel screw mounting

Item number:	17 019 950
EAN:	4103810424403
Discount group:	A

Technical data

Delivery rate (l/stroke):	0,05
Delivery rate at 60 strokes/min (l/min):	3
Barrel screw coupling, female thread:	M 62,5 x 4 female
Pumping media:	oils, up to SAE 140
Usage:	rectangular 20 l original containers or right angled plastic barrels with external thread (M 62,2 x 4 mm)
Application:	for direct filling of gearboxes and difficult to access locations
Discharge:	through discharge hose and steel discharge spout wih lever ball valve
Length of suction tube (mm):	500
Surface treatment:	all steel components are galvanized

Materials of parts in contact with liquid

Pump head:	impact-resistant zinc die casting
Pump body:	steel
Seals:	NBR

Weight (kg):	2,12

Specification

- Discharge hose, 1500 mm, NBR, with textile insert (17 003)
- Barrel screw coupling, for plastic container, height adjustable (19 519)
- Steel discharge spout, with lever ball valve (13 096)
- Packed in single carton box

Special notes

- For oils, up to SAE 140, self-lubricating, non-aggressive media

Packaging

Dimensions LxWxH (mm):	675 x 420 x 100
Weight including package (kg):	2,64
Packing unit:	1,0