

Tank-750 l-FZP 65 l/min-230 V-50 Hz

EUS-ZVABD-4 m

Item number:	23 063
EAN:	
Discount group:	D

Technical data

Tank	
Tank volume (l):	750
External dimensions LxWxH (mm):	980 x 800 x 1720
Material outer container:	steel, hot-dip galvanized
Material of interior container:	HDPE
Filling:	G 2" tank filling coupler
Discharge:	automatic nozzle valve
Pump	
Brand:	FMT Swiss AG
Connecting cable, length (m):	2
Connection suction side:	G 1" i
Connection discharge side:	G 1" i
Hydraulic data	
Pump design:	vane pump, selfpriming
Delivery rate under free discharge (l/min):	65
Suction height (m):	3
Discharge pressure up to (bar):	1,8
Pumping media:	fuel oil and diesel
Motor data	
Voltage (V):	230
Frequency (Hz):	50
Thermal protection:	self resetting
Power consumption (A):	3
Power (kW):	0,6
Torque (Nm):	1,27
Rotation speed (rpm):	2800
Duty cycle (min):	continuous operation – a real endurance runner
Type of construction:	IMB 3
Safety class:	IP66
Materials of parts in contact with liquid	
Seals:	FKM (Viton®)/NBR
Pump housing:	AlSi 12 (sea water resistant)
Rotor:	GG 25
Vane:	POM
Dimensions of pump LxWxH (mm):	280 x 115 x 170
Weight (kg):	93

Specification

- Can not be calibrated for public sales (NEF)
- Vane pump, with integral bypass (23 430)
- Suction set with foot valve
- Discharge hose, 4 m, G 1" male/female
- Storage tank, 750 l, with level indicator and optical leakage indicator (45 101)
- Mounting plate

- Automatic nozzle valve with German design approval and swivel, ZVABD (23 168)
- Universal control nozzle storage bracket (23 174)

Special notes

- Bunded tank
- With steel pallet and level indicator
- Completely assembled on a mounting plate
- With general construction authorities approval no. Z-40.21-288 of German DIBt-Berlin

Packaging

Packing unit: 1,0