

LubeFILL 10 PRO

50-kg-BE-Ø 335-385 mm-4 m-HS

Item number:	19 000 506
EAN:	4103810715259
Discount group:	D

Technical data

Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Grease connection:	coupling plug ISO16028
Container size (kg):	50
Ø follower plate (mm):	335-385
Length of hose (m):	4
Pump data	
Pneumatic data (drive)	
Cylinder capacity engine (cm³):	220
Min. air pressure (bar):	2
Recommended air pressure (bar):	6
Max. air pressure (bar):	8
Air consumption at 8 bar air pressure (l/min):	400
Compressed air connection:	G 1/4" female
Hydraulic data (flow media)	
Cylinder capacity pump (cm³):	22
Pressure ratio:	10:1
Pump pressure at 8 bar air pressure (bar):	80
Pump capacity at 8 bar at a free-flow (g/min):	2000
Grease connection, pressure side:	G 1/2" male
Container emptying:	> 99 %
Conveyed media (specification)	
Pumping media:	lubricating and silicone greases
Supports grease from penetration grade according to ASTM-mill penetration (10^{-1} mm):	NLGI 3 up to 5 °C, NLGI 2 up to 0 °C
Time duration for 1 complete container draining:	50 kg of grease (NLGI 2) in 25 min.
Noise emission	
Noise level, dB(A), idle running acc. to ISO 9614-2 at a distance of 2 m:	78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (dB A):	77
Materials of parts in contact with liquid	
Seals:	FKM, NBR, PU
Pump flange:	zinc alloy
Pump pipe:	steel, galvanized
Design data	
Length of suction tube (mm):	700
Diameter of suction pipe outside (mm):	35
Total length (mm):	832
Max. diameter of pump (mm):	130
Weight (kg):	13,54

Specification

- Pneumatic grease pump 10:1 (18 513 051)
- Stabilising-fixing bracket (17 199)
- Follower plate (17 380)
- Dust cover (17 198)
- Adapter, G 1/2" male, M 20x1,5 male (17 040)
- Adapter, G 1/2" male, M 22x1,5 male (17 040 001)
- Coupling plug flat sealing (17 042)
- Coupling sleeve flat sealing (17 043)
- Double nipple (20 116)
- 2-way ball valve (17 046)
- Adapter, G 1/4" male, G 1/2" male (17 041)
- Discharge hose, 4 m, G 1/2" male/female (19 564)
- Male quick release adapter (20062)
- Pressure reducing valve (pre-set at 8 bar)

Special notes

- High delivery rate of up to 2 kg/minute for fast filling
- Processes lubricating and long-term greases from NLGI 00 up to and including NLGI 3
- Container emptying over 99%
- 5-year warranty on the pneumatic pump (excluding wear parts)
- 10-year guaranteed spare parts availability
- Secure, clean connection thanks to ISO 16028 coupling plug
- Particularly low-maintenance and low-wear design
- Optimum efficiency (air consumption/delivery rate)
- Pump unit can be easily dismantled for cleaning purposes
- Operate pneumatic pump with maintenance unit (oiler and water separator) (20 218 950)

Packaging

Dimensions LxWxH (mm):	1010 x 480 x 270
Weight including package (kg):	14,36
Packing unit:	1,0