





Manually operated high press' grease pump

20-kg-BE-Ø 270-310 mm-SRL 475

Item number:	17 694
EAN:	4103810176944
Discount group:	A

Technical data

Pumping media:	lubricating greases, up to NLGI 2
Delivery rate/stroke (cm³):	3,8
Discharge hose:	high pressure hose, 11 x 1500 mm (12 765 601)
Grease supply:	manually lever operated
Follower plate:	for 20 kg container
Ø follower plate (mm):	270 – 310
Length of suction tube (mm):	475
Discharge pressure up to (bar):	200
Material pump body:	steel
Material pump head:	impact-resistant zinc die casting
Surface treatment:	all steel components are galvanized
Lacquering dust cover:	blue, Pantone 294 C

Specification

- Pump
- Suction tube
- Dust cover (17 176), stabilising-fixing bracket (17 197) and follower plate (17 300)
- High pressure grease hose, 11 x 1500 mm (12 765 601)
- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)
- Robust carrying handle
- Packed in single carton box

Packaging

Dimensions packaging LxWxH (mm):	670 x 420 x 100
Weight including package (kg):	6,07
Packing unit:	1,0