





MKF 6 µm - G 1/8" -400 gr +

500 gr SKT-PZ-MU-EBZD-MAGN

Item number:	12 841 235
EAN:	4103810700781
Discount group:	A

Technical data

Connection discharge side:	G 1/8"
Diameter of grease piston (mm):	10
Max. delivery pressure (bar):	400
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Delivery rate stroke (cm³):	2,2
Filling:	500 g screw-in cartridge (12 524), 400 g screw-in cartridge
Lacquering hand levers:	moss green, RAL 6005
Colour handgrips:	marker green, RAL 1107077
Dimensions LxWxH (mm):	380 x 185 x 30
Weight (kg):	1,08

Specification

- With magnet
- With hose bracket
- High pressure hose, G 1/8" male, 11 x 600 mm, with sealing ring (12 776 828)
- Precision machined coupler, 4 claws, G 1/8" female (12 743)
- In-line meter for grease (18 115)
- Centering ring adapter (88 683 101)
- Grease gun head, zinc die casting Z 410
- Ball seat valve, galvanized (85 627)

Special notes

- Due to the powerful magnet the grease gun can be fixed to metal surfaces to allow one-hand operation
- Supports grease from penetration grade according to ASTM-mill penetration (10^{-1} mm): NLGI 3 till 10°C
- Ergonomic contoured safety handgrip
- Extended product lifetime based on an optimal combination of zinc (grease gun head) and polished steel (reciprocating)
- Unmatched surface Ra (0,4 µm) and tolerance (6 µm) of the piston tube for the main piston - no dummy apparent lubrication
- Optimal leverage for operating the hand lever, thus the force required for lubrication is as low as possible
- All screw connections are sealed
- Quick exchange of cartidges
- Environmental friendly, cartidge can be emptied completely
- Filling level and type of grease visible

Packaging

Dimensions LxWxH (mm):	381 x 192 x 67
Weight including package (kg):	1,2
Pallet Quantity (h = 1,2 m):	168 pcs.
Packing unit:	1,0