mobiBLUE-250 I-ZVMU

24 V-30 l/min



Item number:	26 909
EAN:	4250979602026
Discount group:	D

Technical data

Tank volume (l):	250
Material tank:	LLDPE (linear low density polyethylene)
Color tank:	white
Colour of cover:	blue, RAL 5015



Pump	
Connecting cable, length (m):	3
Hydraulic data	
Pump design:	diaphragm pump, selfpriming
Delivery rate under free discharge (l/min):	30
Discharge pressure up to (bar):	1,7
Pumping media:	AdBlue®, water
Motor data	
Voltage (V):	24 V DC
Power consumption (A):	9
Duty cycle (min) under free discharge max.:	180
Safety class:	IP66
Dimensions LxWxH (mm):	1200 x 800 x 625
Weight (kg):	43

Specification

- Single-walled tank
- Universal fixation loops for integral shackles
- Lockable protection cap
- Tank cap with seal (45 152)
- Ventilation valve (45 150)
- Diaphragm pump, selfpriming (25 282)
- On/Off switch
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- Discharge hose 4 m, DN 19
- Foot valve with filter (23 188)

Special notes

- Movable under load
- Diffusion resistant
- UV-resistant

Packaging

Dimensions LxWxH (mm):	1200 x 800 x 625
Weight including package (kg):	43
Packing unit:	1,0