







mobiBLUE-450 I-ZVMU

24 V-30 l/min

Item number:	26 902
EAN:	4250979602149
Discount group:	D

Technical data

Tank volume (l):	450
Material tank:	LLDPE (linear low density polyethylene)
Color tank:	white
Colour of cover:	blue, RAL 5015
Pump	
Connecting cable, length (m):	3
Hydraulic data	
Pump design:	diaphragm pump, selfpriming
Delivery rate under free discharge (l/min):	30
Discharge pressure up to (bar):	1,7
Pumping media:	AdBlue®, water
Motor data	
Voltage (V):	24 V DC
Power consumption (A):	9
Duty cycle (min) under free discharge max.:	180
Safety class:	IP66
Dimensions LxWxH (mm):	1200 x 800 x 912
Weight (kg):	56

Specification

- Single-walled tank (45 319)
- Universal fixation loops for integral shackles (89 823)
- Lockable protection cap (81 579)
- Ventilation valve (45 150)
- Tank cap with seal (45 152)
- Gas spring kit (45 153)
- Diaphragm pump, selfpriming (25 282)
- On/Off switch
- Connecting cable with battery terminal clips and fuse holder (80 725)
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- AdBlue® discharge hose, DN 19, 4 m / 13.1 ft, with hose fitting G 1" female and swivel joint for ZVMU (25 674)
- AdBlue® suction hose with siphon protection (25 661)

Special notes

- Movable under load
- Diffusion resistant
- UV-resistant
- Transparent tank (fill level is recognizable)
- Can be moved while filled with a forklift or crane
- Compact construction (fits on a Euro pallet)

- Pump area closed with a cover to protect against weather conditions
- High quality equipment
- Manufacturer's warranty on the tank, valid for 5 years from the date of delivery, and 2 years warranty on built-in and attachment parts

Packaging

Dimensions LxWxH (mm):	1200 x 800 x 912
Weight including package (kg):	56
Packing unit:	1,0