



mobiFITT-200 l
ZVABD-24 V-35 l/min-EBZD

Item number:	26 476
EAN:	4250979600374
Discount group:	D

Technical data

Tank volume (l):	200
Material tank:	LLDPE (linear low density polyethylene)
Temperature range (°C):	-10 / +40
UN approval:	un 31H2/Z/** **/CZ/IMET 1526/0/250kg
Pump	
Brand:	FMT Swiss AG
Connecting cable with battery terminal clips, length (m):	3
Hydraulic data	
Pump design:	vane pump, selfpriming
Delivery rate under free discharge (l/min):	35
Discharge pressure up to (bar):	1,6
Pumping media:	Fuel oil, diesel, HVO 100
Motor data	
Digital in-line meter	
Display:	5 digits display
Temperature range (°C):	-10 / +60
Voltage (V):	24 V DC
Power consumption (A):	11
Fuse (A):	25 A plug-in fuse
Duty cycle (min) under free discharge max.:	180
Safety class:	IP66
Run time (min) when dispensing valve is closed max.:	2
Dimensions LxWxH (mm):	1000 x 654 x 547
Weight (kg):	38,5

Specification

- Single-walled tank (45 481)
- Universal fixation loops for integral shackles
- Lockable protection cap
- Ventilation valve (45 140)
- Level indicator (82 601 100)
- Tank cap with seal (45 151)
- Safety valve between tank and pump (19 779)
- Non-return valve with filter (91 146 001)
- Vane pump, with integral bypass (23 405 964)
- On/Off switch
- Automatic nozzle valve with German design approval and swivel, ZVABD (23 168)
- In-line meter, digital (23 190)
- Discharge hose, 3,8 m, DN 19, G 1" male, G 1" female (23 155 967)

Special notes

- Movable under load
- Diffusion resistant
- UV-resistant (UV index 12)
- Manufacturer's warranty on the tank and vane pump (excluding wearable parts), valid for 5 years from the date of delivery, and 2 years warranty on built-in and attachment parts
- Storage of petrol in the tank is strictly forbidden.
- A leakage test is recommended to be effected every 2 1/2 years, a general test every 5 years
- UN/ADR approval for ares® mobiFITT tanks and FMT® diesel pump systems
- UN-approval
- Production under permanent control of the German TÜV

Packaging

Dimensions LxWxH (mm):	1000 x 654 x 547
Weight including package (kg):	38,8
Packing unit:	1,0