

Grease supply system-FB-WA (17 075)

200-kg-BE-Ø 540-590 mm-SAR

Item number:	18 788 561
EAN:	4103810704857
Discount group:	D

Technical data

Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Grease connection:	coupler, for hydraulic grease nipples, DIN 71412
Application:	200-kg-BE-Ø 540-590 mm-SAR
Grease emptying:	99 % grease emptying - 1 % residual grease in the container

Specification

- For 200 kg container, ø 540 - 590 mm
- Pneumatic grease pump 50:1 (18 716 051)
- Special pump mechanism
- Male quick release adapter (20 062)
- Hose reel, open, WB, 10 m (29 242) and trolley (17 075)
- Dust cover, stabilising-fixing bracket and follower plate
- High pressure grease gun (18 104)
- Z-swivel joint (18 082)
- Pressure reducing valve (pre-set at 8 bar)

Special notes

- 99 % grease emptying - 1 % residual grease in the container
- Spare parts available for 10 years
- 5-year warranty on pneumatic pump (excluding wearable parts)
- Operate pneumatic pump with maintenance unit (oiler and water separator) (20 218 950)

Packaging

Dimensions LxWxH (mm):	870 x 760 x 1420
Packing unit:	1,0