

Oil gun-HHÖP

M 10 x 1-GBDR-MU

Item number:	12 602
EAN:	4103810126024
Discount group:	A

Technical data

Oil gun connection - pressure side, with metal adapter:	M 10 x 1
Capacity (ml):	500
Refilling options:	utilising a sealing cap
Diameter oil plunger:	9
Actuation oil plunger:	manual with lever
Delivery rate/stroke (cm³):	proportional to the manual lever operating distance, max. 1,6
Max. delivery pressure (bar):	400
Burst pressure system (bar):	850
Burst pressure oil gun head (bar):	1200
Wall thickness pipe (mm):	1
Lacquering:	silver
Weight (kg):	1,23

Specification

- Angled spout, M 10 x 1, 150 mm (12 635)
- Coupler, 4 jaws, M 10 x 1, with ball valve (12 642)
- Sales package, with Bar code

Special notes

- With double plunger with leak-proof construction for oils and liquid greases (NLGI 00-000)
- Chain retrieval of two-way plunger
- Pump piston with high accuracy of fit to the cylinder
- No dummy (apparent) lubrication. Sealing system: O-ring and ball valve prevent oil compressed in the oil gun head from feeding back.
- Performance unchanged after 40.000 actuating cycles
- Oil gun head and sealing cap, zinc die casting Z 410
- Slip-proof handle on the lever of the lever oil gun
- Allows lubrication in difficult to reach locations because the smallest lever operation results in oil being pumped reliably to the lubrication point.
- Enables even under extreme backpressure, a variable lubrication pressure with steady effort applied

Packaging

Dimensions LxWxH (mm):	390 x 125 x 66
Weight including package (kg):	1,35
Packing unit:	1,0