

Pneumatic diaphragm pump

110 l/min

Item number:	19 061
EAN:	4103810190612
Discount group:	D

Technical data

Delivery rate under free discharge (l/min):	110 (water)
Max. air pressure (bar):	8
Min. air pressure (bar):	2
Max. particle size (mm):	3,5
Max. suction height, dry (m):	6
Max. suction height, wet (m):	9,8
Max. discharge height (m):	80
Max. operating temperature (°C):	65
Min. operating temperature (°C):	-4
Loudness level at 3,5 bar (dB A):	72
Max. air consumption (l/min):	depending on delivery volume and delivery head
Connection air:	3/8" BSP
Connection suction side:	3/4" BSP
Connection discharge side:	3/4" BSP
Material pump housing:	PP
Material air diaphragm:	Hytrel®
Material fluid diaphragm:	PTFE
Material ball:	PTFE
Material ball valve seat:	PP
Material O-rings:	FPM
Dimensions LxWxH (mm):	265 x 175 x 245
Weight (kg):	6,5

Specification

- Fixture, for wall-mounting
- Accessories required:
- Wall mounting bracket (87 918)
- Male quick release adapter (20 064)
- Suitable for:
- Fresh and waste oils, water, AdBlue®
- Water-based liquids, to which PP and PTFE are resistant, e.g. glass cleaner and radiator antifreeze agents

Packaging

Dimensions LxWxH (mm):	320 x 200 x 310
Weight including package (kg):	7
Packing unit:	1,0