

Pneumatic pump 3:1

Alu-INOX-for wall-mounting

Item number:	19 285 843
EAN:	4103810715082
Discount group:	D

Technical data

Pressure ratio:	3:1
Max. diameter (mm):	75
Max. air pressure (bar):	10
Min. air pressure (bar):	3
Recommended air pressure (bar):	8
Cylinder capacity engine (cm³):	230
Quantity of strokes at 8 bar at a free-flow (strokes/min):	250
Pump capacity at 8 bar at a free-flow (l/min):	23
Pump pressure at 8 bar air pressure (bar):	24
Air consumption at 8 bar air pressure (l/min):	800
Length of discharge pipe work:	depends on size of installation.
Max. suction height (m):	6
Compressed air connection:	G 1/4" female
Oil connection - suction side:	G 1" male
Oil connection - delivery side:	G 3/4" female
Connection container:	G 2" male, drum adapter
Sound level when operating at a distance of 1 m (db A):	101
Viscosity of discharged liquid:	oil up to SAE 90
Classical liquids to be discharged:	gear oil, glycol, windscreen cleaner and water
Material pump housing:	aluminium
Material of suction tube:	PVC
Materials of parts in contact with liquid:	stainless steel, brass, plastic
Seals:	Viton® (FKM)
Length of engine (mm):	420
Weight (kg):	3,5

Specification

- Pneumatic pump 3:1, aluminium/stainless steel, for windscreen cleaners
- Wall mounting
- Suction tube, G 1 female
- Can be easily combined with several hose reels
- Packed in carton box

Special notes

- Operate pneumatic pump with maintenance unit (oiler and water separator) (20 218 950)

Packaging

Dimensions LxWxH (mm)	
Weight (kg)	
Packing unit:	1,0