

## PRELIxx ONE G 1/8"

FN-black-ZBH-Set 4

| | |
|---|---|
| **Item number:** | 14 412 212 |
| **EAN:** | 4103810704703 |
| **Discount group:** | A |

### Technical data

| | |
|---|---|
| Grease gun connection, pressure-side: | G 1/8" |
| Filling nipple: | M 10 x 1 |
| Capacity (cm³): | 500 |
| Refilling options: | 400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease |
| Diameter of grease piston (mm): | 9 |
| Grease pump piston actuation: | manual, by means of pressure grip |
| | |
| Calibration Volume | |
| Delivery rate/stroke (cm³): | 1,1 |
| Max. delivery pressure (bar): | 200 |
| | |
| Calibration Pressure | |
| Delivery rate/stroke (cm³): | 0,7 |
| Max. delivery pressure (bar): | 300 |
| | |
| Grease gun tube colour: | black |
| Dimensions LxWxH (mm): | 400 x 165 x 66 |
| Weight (kg): | 1,34 |

### Specification

- With hose bracket
- Filling nipple (FN), M 10 x 1 male (12 670)
- Grease gun head, zinc die casting Z 410
- Dismantleable and movable push rod system
- T-grip, optimized grip and pressure optimized
- Ergonomic handle, non-slip, excellent power transfer and handling
- Packed in single carton box
- Precision machined coupler, 4 claws, G 1/8" female (12 743)
- Galvanized parts: grip, lever, pulling strap, safety catch, cap, push rod
- Grease gun also available in the colors silver, red, blue, green and yellow
- Spout, angled, G 1/8", 150 mm (12 735)

### Special notes

- TÜV SÜD-certified
- With the GS mark for Tested Safety (Cert. No. Z1A 102500 0001)
- The construction allows a single hand operated lubrication for an easy work in restricted areas
- Can be switched with the hand grip from grease delivery with high volume to high pressure
- Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions
- Damaged cartridges can easily be removed
- Push rod can be locked in any position - push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)

- The ease of dismantling permits simple cleaning
- Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns
- High-speed ventilation, by half a rotation of the grease gun tube
- Designed for use in rough conditions
- Similar to DIN 1283

**Packaging**

| | |
|---|---|
| Dimensions LxWxH (mm): | 400 x 165 x 75 |
| Weight including package (kg): | 1,49 |
| Packing unit: | 1,0 |