

PRELIxx ONE M 10 x 1

FN-black-ZBH-Set 3

Item number:	14 411 211
EAN:	4103810704567
Discount group:	A

Technical data

Grease gun connection, pressure-side:	M 10 x 1
Filling nipple:	M 10 x 1
Capacity (cm³):	500
Refilling options:	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Diameter of grease piston (mm):	9
Grease pump piston actuation:	manual, by means of pressure grip
Calibration Volume	
Delivery rate/stroke (cm³):	1,1
Max. delivery pressure (bar):	200
Calibration Pressure	
Delivery rate/stroke (cm³):	0,7
Max. delivery pressure (bar):	300
Grease gun tube colour:	black
Dimensions LxWxH (mm):	400 x 165 x 66
Weight (kg):	1,34

Specification

- With hose bracket
- Filling nipple (FN), M 10 x 1 male (12 670)
- Grease gun head, zinc die casting Z 410
- Dismantleable and movable push rod system
- T-grip, optimized grip and pressure optimized
- Ergonomic handle, non-slip, excellent power transfer and handling
- Packed in single carton box
- Precision machined coupler, 4 claws, M 10 x 1 female (12 643)
- Galvanized parts: grip, lever, pulling strap, safety catch, cap, push rod
- Grease gun also available in the colors silver, red, blue, green and yellow
- Angled spout, M 10 x 1, 150 mm (12 635)

Special notes

- TÜV SÜD-certified
- With the GS mark for Tested Safety (Cert. No. Z1A 102500 0001)
- The construction allows a single hand operated lubrication for an easy work in restricted areas
- Can be switched with the hand grip from grease delivery with high volume to high pressure
- Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions
- Damaged cartridges can easily be removed
- Push rod can be locked in any position - push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)

- The ease of dismantling permits simple cleaning
- Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns
- High-speed ventilation, by half a rotation of the grease gun tube
- Designed for use in rough conditions
- Similar to DIN 1283

Packaging

Dimensions LxWxH (mm):	400 x 165 x 75
Weight including package (kg):	1,49
Packing unit:	1,0