







PREMAxx 35 l/min-9.2 gpm - AdBlue®

12 V-DC-ABK-ZVMU-4 m

Item number:	23 761
EAN:	4048358237613
Discount group:	D

Technical data

Connecting cable with battery terminal clips, length (m) / (ft):	2 / 6.6
Connection container:	G 2" male, drum adapter
Connection suction side:	G 1" male
Connection discharge side:	G 1" male
Hydraulic data	
Pump design:	axial gear
Delivery rate under free discharge up to (l/min) / (gpm):	35 / 9.2
Suction height up to (m) / (ft):	2,5 / 8.2
Discharge height max. (m) / (ft):	15 / 49.2
Pumping media:	AdBlue®, water, antifreeze
Motor data	
Voltage (V):	12 V DC
Power consumption (A):	14
Power (W):	180
Thermal protection:	self resetting
Duty cycle (min):	30
Rotation speed at 0,5 bar counterpressure (rpm):	7500
Type of construction:	IMB 5
Safety class:	IP34
Material of pump housing and pump:	PA 6
Material motor shaft:	stainless steel 1.4021
Dimensions of pump LxWxH (mm) / (inch):	90 x 120 x 300 / 3.5 x 4.7 x 11.8
Weight with accessories (kg) / (lb):	4,5 / 9.9

Specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 760)
- Illuminated on/off switch
- Motor with thermal protection switch, self resetting
- Connecting cable with battery terminal clips and fuse holder (80 725)
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- AdBlue® discharge hose, DN 19, 4 m / 13.1 ft, with hose fitting G 1" female (25 191 400)
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm or from 14 to 38 inches)
- Suction strainer, (13 097 002), optional for telescopic suction tube (13 094)
- Fassadapter, G 2" male (13 085 100)
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged



- Can be manually operated in case of electric power blackout
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation and changing by screw coupling
- Can be freely positioned in 30° increments
- Optional barrel adapters: (13 085 101) barrel adapter S 56x4; (13 085 102) barrel adapter S 69,5x5,5; (13 085 103) barrel adapter M 64x4 male; (13 085 106) barrel adapter S 64x5
- Telescopic suction tube, flexible length

Packaging

Packaging:	Carton
Dimensions LxWxH (mm) / (inch):	400 x 400 x 220 / 15.7 x 15.7 x 8.7
Weight including package (kg) / (lb):	5,31 / 11.7
Packing unit:	1,0



