








## PREMAxx 35 l/min-9.2 gpm

24 V-DC-ABK

| | |
|---|---|
| **Item number:** | 23 720 |
| **EAN:** | 4048358237200 |
| **Discount group:** | D |

### Technical data

| | |
|---|---|
| Connecting cable with battery terminal clips, length (m) / (ft): | 2 / 6.6 |
| Connection container: | G 2" male, drum adapter |
| Connection suction side: | G 1" male |
| Connection discharge side: | G 1" male |

| | |
|---|---|
| Hydraulic data | |
| Pumping media: | fuel oil and diesel |
| Pump design: | axial gear |
| Delivery rate under free discharge up to (l/min) / (gpm): | 35 / 9.2 |
| Suction height up to (m) / (ft): | 2,5 / 8.2 |
| Discharge height max. (m) / (ft): | 15 / 49.2 |
| Operating temperature (°C): | -10 ... +40 |
| Bypass mode max. (min): | 2 |
| dry run maximum: | 2 |
| Noise Development (dBA) according to ISO: | 76 |

| | |
|---|---|
| Motor data | |
| Voltage (V): | 24 V DC |
| Power consumption (A): | 10 |
| Power (W): | 240 |
| Thermal protection: | self resetting |
| Duty cycle (min): | 30 |
| Rotation speed at 0,5 bar counterpressure (rpm): | 7500 |
| Type of construction: | IMB 5 |
| Safety class: | IP34 |

| | |
|---|---|
| Material of pump housing and pump: | PA 6 |

| | |
|---|---|
| Dimensions LxWxH (mm) / (inch): | 130 x 130 x 350 / 5.1 x 5.1 x 13.7 |
| Weight with accessories (kg) / (lb): | 2,5 / 5.5 |

### Specification

- For 200 up to 1000 l container
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Motor with thermal protection switch, self resetting
- Battery terminal clips, 2 m cable
- Illuminated on/off switch
- Valuable sales package

### Special notes

- The pump is lightweight and very quiet in operation.



- Resistant against small dirt particles in the liquid to be discharged
- Can be manually operated in case of electric power blackout
- Pump can be used with compact systems up to 1000 l (45 100) with adapter (88 851)

**Packaging**

| | |
|---|---|
| Dimensions LxWxH (mm) / (inch): | 330 x 260 x 220 / 12.9 x 10.2 x 8.6 |
| Weight including package (kg) / (lb): | 2,7 / 6 |
| Packing unit: | 1,0 |











