

Compact system-1500 l

oil pump-230 V-SAR-15 m-O-WB

Item number:	23 004 351
EAN:	
Discount group:	D

Technical data

Tank	
Tank volume (l):	1500
Material outer container:	steel, hot-dip galvanized
Material of interior container:	HDPE
Connections:	4 x G 2" female, drum adapter
External dimensions LxWxH (mm):	1630 x 800 x 2200
Empty weight (kg):	151
Filling:	G 2" tank filling coupler
Application:	for above ground storage of fresh oils
Oil discharge:	electrical oil pump
Brand:	FMT Swiss AG
Connecting cable, length (m):	1,8
Connection suction side:	G 3/4" male
Connection discharge side:	G 1/2" male
Hydraulic data	
Pump design:	gearwheel pump, selfpriming
Delivery rate under free discharge (l/min):	10
Suction height (m):	3,5
Discharge pressure up to (bar):	10
Pumping media:	oils up to SAE 90
Motor data	
Voltage (V):	230
Frequency (Hz):	50
Power consumption (A):	4,5
Power (W):	750
Thermal protection:	self resetting
Duty cycle (min):	continuous operation – a real endurance runner
Torque (Nm):	2
Rotation speed (rpm):	1450
Type of construction:	IMB 3
Safety class:	IP66
Dimensions of pump LxWxH (mm):	310 x 195 x 205
Weight of motor and pump (kg):	13
Dispensing:	Digital hose end meter

Specification

- Oil pump (23 337)
- Hose reel, open, WB, 15 m (29 143)
- Suction tube set
- Check valve (84 546)
- Mounting plate (88 118)
- Tank, 1500 l, with level indicator and visual leakage indicator (45 105)
- With hose end meter, digital (19 698 950), swivel joint, anti-drip nozzle
- Storage bracket for hose end meter, integral drip tray (29 980)

Special notes

- Completely assembled on a mounting plate
- Bunded tank
- With general construction authorities approval no. Z-40.21-283 of German DIBt-Berlin
- For above ground storage in closed rooms
- Integral handles
- Steel pallet foot, fully detachable

Packaging

Packing unit: 1,0