

Hose reel-coolant

GDA-WB-120 bar-DN 12-15 m

Item number:	29 573
EAN:	4103810295737
Discount group:	D

Technical data

Length of discharge hose (m):	15
Connection discharge hose:	G 1/2" male/female
Length of connecting hose (m):	1
Connection to connecting hose:	G 1/2" female/female
Inner diameter of hose (DN):	12
Operating pressure max. (bar):	120
Lacquering	
Casing:	window grey, satin, RAL 7040
Arm:	window grey, satin, RAL 7040
Supporting plate:	window grey, satin, RAL 7040
Encasing:	blue, Pantone 294 C
Panel:	blue, Pantone 294 C
Dimensions LxWxH (mm):	495 x 158 x 508
Weight (kg):	26,100

Specification

- Hose reel for cooling liquids
- Encased, for wall/floor mounting, outside swivel
- With hose stop

Special notes

- Pressol hose reels are exceedingly robust and are notable for their compact design
- All metal parts are phosphatized, undercoated and painted
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum
- The hose can be engaged by rotating 1/4 turn

Packaging

Dimensions LxWxH (mm):	540 x 580 x 160
Weight (kg):	26,900
Packing unit:	1,0