

Waste oil drainer unit-95 l

mobile-compressed air evac.

Item number:	27 070 890
EAN:	4103810428968
Discount group:	D

Technical data

Total volume (l):	95
Telescopic height level of drain bowl (mm):	1340 - 1910
Volume of drain bowl (l):	18
Diameter drain bowl (mm):	420
Discharge:	by compressed air
Connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Lacquering of container:	window grey, satin, RAL 7040
Lacquering of drain bowl:	blue, Pantone 294 C
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	600 x 580 x 1310
Weight (kg):	31,2

Specification

- Overpressure safety valve, set at 0.5 bar, with a pressure regulating valve
- Male quick release adapter (20 062)
- Transparent discharge hose, 2 m, with metal discharge spout
- 2 fixed rear wheels, 2 castor front wheels
- Drain bowl with removable strainer and drain grill
- Lever ball valve in the filling spout
- Sturdy handle
- Pressure discharge
- Container made from 1,5 mm sheet steel
- With metal protective cover to avoid damage
- Lacquered with oil-resistant hydro-structure paint
- With height adjustable drain bowl

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)
- If the waste oil drainer is discharged via a pipe system into an oil collection tank, it is recommended to use an overflow protection valve. Please adhere to regional regulations and guidelines of your country

Packaging

Dimensions LxWxH (mm):	630 x 580 x 1000
Weight (kg):	33
Packing unit:	1,0