

Waste oil drainer/-suction unit-95 l

venturi-mobile

Item number:	27 622 891
EAN:	4103810428982
Discount group:	D

Technical data

Total volume (l):	95
Height range of drain funnel:	1550 - 2120
Diameter drain bowl (mm):	420
Volume of drain bowl (l):	18
2 compressed air connections:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Recommended air pressure (bar):	6
Suction rate probe Ø 5 mm (l/min):	1,0 - 1,5
Suction rate probe Ø 6 mm (l/min):	2,0 - 2,5
Suction rate probe Ø 8 mm (l/min):	3,5 - 4,0
Min. oil temperature (°C):	70
Lacquering of container:	window grey, satin, RAL 7040
Lacquering of drain bowl:	blue, Pantone 294 C
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	600 x 580 x 1150

Specification

- A vacuum is generated in the container by means of a venturi system and compressed air
- Manometer / vacuum meter, for pressure and vacuum level indication
- Oil extraction through the dipstick tube
- Level indicator
- Overpressure safety valve, set at 0.5 bar, with a pressure regulating valve
- Male quick release adapter for Rectus coupler, type 26, NW 7,2 mm (20 062), lever ball valve
- Suction hose, 2 m, with spiral spring
- Suction probes, Ø 5 / 6 / 8 mm
- With adapters for BMW, Mercedes, VW, Audi and Smart
- Suction probe holder
- Transparent discharge hose, 2 m, with metal discharge spout and lever ball valve
- Drain bowl with removable strainer and drain grill
- Sturdy handle
- 2 fixed rear wheels, 2 castor front wheels
- Pressure discharge
- Container made from 1,5 mm sheet steel
- With metal protective cover to avoid damage
- Lacquered with oil-resistant hydro-structure paint
- With height adjustable drain bowl
- Spare parts, see at Venturi-system (04 426)

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)
- If the waste oil drainer is discharged via a pipe system into an oil collection tank, it is recommended to use an overflow protection valve. Please adhere to regional regulations and guidelines of your country

Packaging

Dimensions LxWxH (mm):	780 x 580 x 630
Weight (kg):	38,380
Packing unit:	1,0