

Waste oil disposal system for
inspection pits-diaphragm pump

Item number:	19 000 435
EAN:	4103810715099
Discount group:	D

Technical data

Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Connection pressure hose:	G 1/2" female, 60° sealing cone, 90° tube turn
Drainage tray	
Capacity (l):	60
Track width (mm):	850 - 1200
Connection:	G 3/4" male thread (both sides)
Lacquering:	window grey, satin, RAL 7040
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	760 x 460 x 200
Weight (kg):	25,8

Specification

- For the entire vehicle and commercial vehicle areas
- Suction hose, 2 m, G 3/4" male/female (19 512)
- Pressure hose, 1,5 m, G 1/2" female/male
- With pneumatic diaphragm pump (19 060), capacity 55 l/min under free discharge, suitable for pipe-works up to 20 m
- Wall mounting bracket (87 626)
- With all required adapters, couplings, etc.
- Drain tray (19 788), suitable for all standard garage service pit profiles

Special notes

- Always use a flexible metal hose (19 666) for pipework connection in non-visible areas. For installation please adhere to regional regulations and guidelines. It is recommended, acc. to German govt. specifications, to install an overflow protection valve if waste oil discharge shall be effected by using a fixed pipework installation. Adhere to regional regulations and guidelines in any case.

Packaging

Dimensions LxWxH (mm):	960 x 570 x 340
Weight (kg):	25,860
Packing unit:	1,0