

Standard grease gun-HHFP

G 1/8" -GBDR-MU

Item number:	12 632 125
EAN:	4103810127328
Discount group:	A

Technical data

Grease gun connection, pressure-side:	G 1/8"
Capacity (cm³):	500
Refilling options:	400 g grease cartridge, DIN 1284, or bulk grease using a spatula
Diameter of grease piston (mm):	8
Grease pump piston actuation:	manually lever operated
Delivery rate/stroke (cm³):	1,2 at a grease density of 0.92 kg/dm³, tested with grease cartridge 400 g (12 511)
Discharge pressure up to (bar):	400
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Operation of push rod:	with L-design handle
Cover:	loose
Wall thickness of grease gun tube (mm):	1,0
Lacquering:	silver
Dimensions LxWxH (mm):	395 x 120 x 66
Weight (kg):	1,25

Specification

- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)

Special notes

- TÜV SÜD-certified
- With the GS mark for Tested Safety (Cert. No. Z1A 102500 0001)
- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Package:	Polybag, printed, with EAN bar code
Dimensions LxWxH (mm):	400 x 360 x 145
Weight including package (kg):	13,2
Packing unit:	10,0