

Standard grease gun-HHFP

G 1/8" -FN-GBDR-MU-VVP

Item number:	12 734 804
EAN:	4103810427213
Discount group:	A

Technical data

Grease gun connection, pressure-side:	G 1/8"
Filling nipple:	M 10 x 1
Capacity (cm³):	500
Refilling options:	400 g grease cartridge, DIN 1284, or bulk grease
Diameter of grease piston (mm):	8
Grease pump piston actuation HHFP:	manually lever operated
Delivery rate/stroke (cm³):	1,2, at a counter-pressure of 400 bar
Discharge pressure up to (bar):	400
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Operation of push rod:	with L-design handle
Cover:	loose
Wall thickness of grease gun tube (mm):	1
Lacquering:	silver
Weight (kg):	1,28

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)
- Sales package, with Bar code

Special notes

- TÜV SÜD-certified
- With the GS mark for Tested Safety (Cert. No. Z1A 102500 0001)
- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm):	400 x 140 x 75
Weight including package (kg):	1,38
Packing unit:	1,0