

Standard grease gun-HHFP-1000 cm³

M 10 x 1-FN-VDF

Item number:	12 686 782
EAN:	4103810423352
Discount group:	A

Technical data

Grease gun connection, pressure-side:	M 10 x 1
Filling nipple:	M 10 x 1
Capacity (cm³):	1000
Refilling options:	400 g grease cartridge, DIN 1284, grease filling system or loose grease using a spatula
Diameter of grease piston (mm):	8
Grease pump piston actuation:	manually lever operated
Delivery rate/stroke (cm³):	1,2, at a counter-pressure of 400 bar
Discharge pressure up to (bar):	400
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Operation of push rod:	with T-grip
Cover:	fixed
Wall thickness of grease gun tube (mm):	1,0
Lacquering:	graphite-grey

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Packed in polybag

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Separate filling and ventilation valves on grease gun head
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- The ergonomic handle of the plunger rod assists in overcoming the spring load
- Slip resistant handle on grease gun lever
- Fixed cap, with clamp
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm):	600 x 125 x 70
Weight including package (kg):	1,7
Packing unit:	1,0