OILMAxx-SR-FZP-4 m-FS

SRL 1600-200/220-I-BE-TA-FV-EBZD-AS





Item number:	23 316 561
EAN:	4048358717979
Discount group:	D

Technical data

Suction hose length (mm):	1600
Connecting thread:	G 2" male, drum adapter
Oil discharge:	electrical oil pump
Pump design:	vane pump
Voltage (V):	230
Power connection:	euro two-pin plug, 1,8 m cable
Connection power (kW):	1,2
Frequency (Hz):	50
Power consumption (A):	5
Delivery rate under free discharge (l/min):	30
Nominal operating pressure (bar):	1
Operating pressure max. (bar):	6
Pumping media:	oils up to SAE 80
Operating temperature area (°C):	+10 / +50
Safety class:	IP66
Weight (kg):	15

Specification

- Stationary oil system
- For 200/220 l container and mounting on tanks
- Electrical oil pump (23 301)
- In-line meter, digital (23 190)
- Discharge hose, 4 m, DN 25, G 1" male, G 1" female (23 155 950)
- Filling valve with swivel (19 701)
- Foot valve with filter (19 890)
- Suction hose, 1,6 m, DN 25, G 1" male, G 1" female (23 156)
- Control nozzle storage bracket with drip tray
- With bend 90° and swivel joint

Special notes

- High-performance pump for transferring gear and engine oils
- Vane pump, with integral bypass
- First class construction of electric machines and pumps
- Designed for a long service life
- Motor and switch case made of shock resistant, die-cast aluminium
- continuous operation – a real endurance runner
- Small tolerances provide a high suction- and pressure performance at best efficiency
- Oval gear meter (calibratable) with a measuring accuracy of +/- 0.5%
- Filling valve with swivel joint (DG) and manual shut-off

Packaging

Packing unit:	1,0