

## Two-hand grease gun 6 µm-G 1/8"

500 gr SKT

| | |
|---|---|
| **Item number:** | 12 852 125 |
| **EAN:** | 4103810700828 |
| **Discount group:** | A |

### Technical data

| | |
|---|---|
| Connection discharge side: | G 1/8" |
| Diameter of grease piston (mm): | 10 |
| Max. delivery pressure (bar): | 400 |
| Burst pressure system (bar): | 850 |
| Burst pressure grease gun head (bar): | 1200 |
| Delivery rate stroke (cm³): | 2,2 |
| Filling: | 500-g-screw-in cartridge (12 524) |
| Lacquering hand levers: | moss green, RAL 6005 |
| Colour handgrips: | marker green, RAL 1107077 |
| Dimensions LxWxH (mm): | 380 x 185 x 30 |
| Weight (kg): | 0,85 |

### Specification

- With hose bracket (86 961 101)
- Grease gun head, zinc die casting Z 410
- Ball seat valve, galvanized (85 627)

### Special notes

- TÜV SÜD-certified
- With the GS mark for Tested Safety (Cert. No. Z1A 102500 0001)
- Particularly suitable for long-term and high-performance lubricating greases, even at low temperatures
- Supports grease from penetration grade according to ASTM-mill penetration ($10^{-1}$ mm): NLGI 3 till 10°C
- Ergonomic contoured safety handgrip
- Extended product lifetime based on an optimal combination of zinc (grease gun head) and polished steel (reciprocating)
- Unmatched surface Ra (0,4 µm) and tolerance (6 µm) of the piston tube for the main piston - no dummy apparent lubrication
- Optimal leverage for operating the hand lever, thus the force required for lubrication is as low as possible
- All screw connections are sealed
- Quick exchange of cartidges
- Environmental friendly, cartidge can be emptied completely
- Filling level and type of grease visible

### Packaging

| | |
|---|---|
| Dimensions LxWxH (mm): | 381 x 181 x 31 |
| Weight including package (kg): | 1 |
| Pallet Quantity (h = 1,2 m): | 300 pcs. |
| Packing unit: | 1,0 |