

Compressed air grease gun-DLkombi

M 10 x 1-PZ-GBDR-2 x MU

Item number:	18 074
EAN:	4103810180743
Discount group:	D

Technical data

Grease gun connection, pressure-side:	M 10 x 1
Filling nipple:	M 10 x 1
Capacity (cm³):	500
Refilling options DLFP:	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Refilling options HHFP:	400 g grease cartridge, DIN 1284, or bulk grease
Pressure ratio DLFP:	50:1
Grease supply into the grease gun head:	spring operated
Diameter of grease piston DLFP (mm):	6
Grease pump piston actuation DLFP:	single-stroke grease supply
Delivery rate/stroke DLFP (cm³):	0,8
Recommended air pressure (bar):	6
Min. air pressure (bar):	2
Max. air pressure (bar):	8
Compressed air connection:	hose nozzle, 6 mm, for hose, DN 6 (20 132)
Pump pressure at 8 bar air pressure (bar):	400
Diameter of grease piston HHFP (mm):	8
Grease pump piston actuation HHFP:	manually lever operated
Delivery rate/stroke HHFP (cm³):	1,2, at a counter-pressure of 400 bar
Operating pressure HHFP (bar):	up to 400 bar
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Operation of push rod:	with L-design handle
Cover:	loose
Wall thickness of grease gun tube (mm):	1,0
Lacquering:	silver
Weight (kg):	2,42

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- With additional grease gun head and lever assembly for conversion to lever operation
- High pressure hose, M 10 x 1 male, 8 x 300 mm (12 656)
- Angled spout, M 10 x 1, 150 mm (12 635)
- 2 hydraulic couplers, 4 jaws, M 10 x 1 (12 631)
- Sales package, with Bar code

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod

- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm):	402 x 171 x 84
Weight including package (kg):	2,568
Packing unit:	1,0