

Waste oil drainer/-suction unit-80 l

venturi-mobile-with GMZ

Item number:	19 793 391
EAN:	
Discount group:	D

Technical data

Total volume (l):	80
Capacity of storage container (l):	15
2 compressed air connections:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Recommended air pressure (bar):	6
Min. oil temperature (°C):	70
Lacquering of container:	window grey, satin, RAL 7040
Lacquering of container storage unit:	blue, Pantone 294 C
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	500 x 500 x 1700

Specification

- With visual inspection reservoir, 10 l
- A vacuum is generated in the container by means of a venturi system and compressed air
- Manometer for pressure indication
- Suction is done via the dipstick tube.
- Suction hose, 2 m, with spiral spring
- 4 suction probes, 2 pcs. each, Ø 5/8 mm
- With adapters for BMW, Mercedes, VW and Audi
- Transparent discharge hose, 2 m, with metal discharge spout
- Rectangular, cantilever drain tray with drain grill, can be lowered to floor level and can be drained via Venturi-technique
- Pressure discharge
- Overpressure safety valve, set at 0.5 bar
- male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
- Overflow protection and probe holder
- Sturdy handle
- 2 fixed rear wheels, 2 castor front wheels

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)
- If the waste oil drainer is discharged via a pipe system into an oil collection tank, it is recommended to use an overflow protection valve. Please adhere to regional regulations and guidelines of your country

Packaging

Dimensions LxWxH (mm):	1700 x 600 x 600
Weight (kg):	61,000
Packing unit:	1,0