

Venturi-waste oil suction unit-24 l

mobile

Item number:	19 782
EAN:	4103810197826
Discount group:	D

Technical data

Total volume (l):	24
Compressed air connection:	male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Recommended air pressure (bar):	6
Vacuum generation time (min):	1 - 2
Suction volume per vacuum build up (l):	8 - 12
Suction rate probe Ø 5 mm (l/min):	1,0 - 1,5
Suction rate probe Ø 6 mm (l/min):	2,0 - 2,5
Suction rate probe Ø 8 mm (l/min):	3,5 - 4,0
Min. oil temperature (°C):	70
Lacquering of container:	window grey, satin, RAL 7040
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	380 x 380 x 950

Specification

- A vacuum is generated in the container by means of a venturi system and compressed air
- Manometer for pressure indication
- Suction is done via the dipstick tube.
- male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
- Suction probes, Ø 5 / 6 / 8 mm
- With adapters for BMW, Mercedes, VW and Audi
- Carrying handle
- Hose, 1700 mm
- 2 fixed rear wheels
- Drainage via screw cap, G 1 1/2"

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)

Packaging

Dimensions LxWxH (mm):	380 x 360 x 950
Weight (kg):	9,94
Packing unit:	1,0